

Roughneck II™ pumless drain - when only the best for your shop will do



Balcrank has been manufacturing lube equipment for over 100 years. The Roughneck II™ is the fast and affordable way to capture used fluids and transfer it into any bulk storage tank using regular shop air.

- Patented automatic fluid evacuation valve eliminates gravity draining, poring, or the need for an evacuation pump
- 23 gallon storage tank; fewer drain intervals
- Pressure safety valve; prevents over pressurization of tank
- Clear evacuation hose; provides fast fluid evacuation and shows fluid levels in tank
- NFPA approved design; meets local and state regulation
- Accessories included; S-hooks for handing technicians tools, front non-marking casters, and large rear 10 inch tires

Roughneck II™ Pumpsless Drain

The Roughneck II™ Series drain is the fast, affordable way to capture used fluid and transfer it into any bulk storage tank or drum using regular shop air. The Roughneck II™ has a patented automatic fluid evacuation valve (US Patent 5,921,262) which eliminates gravity draining, pouring, or the need for an evacuation pump. A seven-foot, quick-disconnect hose remains with the 23 gallon storage tank, keeping it out of the way until it is ready to be used again. A low pressure safety valve prevents over-pressurization, s-hooks are provided allow for hanging tool from bowl for quick retrieval and the clear evacuation-hose doubles as a sight level tube showing the fluid level in the steel tank. The Roughneck II™ features non-marking large 10-inch rubber wheels and extra-wide rubber 4-inch front casters to maneuver over the toughest shop floors. The Roughneck II™ is a NFPA approved design. It is delivered in black for used oils and green for used antifreeze unless otherwise requested. Other colors available are blue, yellow, silver, white and red, (two-week lead time requested on special color requests).



4110-022 - Used Oil Drain

19.25" diameter catch basin features an inlet filter screen and s-hooks for tools.

"Splashguard" bowl design prevents splattering, speeds drainage.

Fully adjustable bowl height from 47 to 74 inches.

One touch operation. No ball valves required for evacuation of fluid.

Roughneck outlet tube mounts securely into bulk used oil reservoir or can be dry-break mounted.

Seven foot evacuation tube provides sight gauge for fluid level.

Tank handle makes maneuvering easy.

Heavy gauge, all-steel construction guarantees long life.

Tip-resistant balanced design.

Large diameter rear rubber wheels and non-marking wide front casters maneuver the toughest shop floors.



4110-022 - Used Antifreeze Drain