

## Overview

Director Jr. manages 1 fluid for up to 10 dispense points. Simple, easy to install and use, the Director Jr. has been in use since 1987. Typical customers include small garages, dealerships, and small equipment service.



### MODEL AVAILABLE



**3110-031**

Director Jr Console V DC

### COMPONENT TECHNICAL DATA

Function	Monitor and control fluid dispense
Requirements & Limitations	non-shielded (for use with solenoid) shielded (for use with impulse meter) 18 gauge wire up to 400' 16 gauge wire 400'-600'
Power	Input -110 VAC - Output - 24 V DC

## Director Jr. Description

- 1.1. The Director Jr. is a console designed to monitor and control fluid dispenses in a workshop from a single central location
- 1.2. The Director Jr. will also manage a solenoid valve to control the air powering the pump.
- 1.3. 1 fluid to 10 stations.
- 1.4. Fluid measurement in pints, quarts, gallons, or liters.
- 1.5. Service fluids: motor oils, synthetics, ATF, gear oils, and Anti-freeze (Glycol).
- 1.6. Totalizing feature for ease of fluid inventory record-keeping.
- 1.7. Large LED information display.

Contact Balcrank customer service for V AC units.

## Director Jr. Specifications:

- 2.1. All Director Jr. consoles will monitor and control a single fluid dispense
- 2.2. All Director Jr. consoles will have 18 gauge wire up to 400' and non-shielded 16 gauge wire from 400' to 600'
- 2.3. All Director Jr. consoles will have 110 VAC power input and 24 VDC power output
- 2.4. All Director Jr. consoles will require the use of Balcrank air solenoid valves, fluid solenoid valves and impulse meter 3120-114 to complete a Director Jr. system.

## Warranty

- 3.1. The Director Jr. components will have a 1-year replacement only warranty (defects in materials and workmanship only).