



Overview

- The standard keypads are designed to be located in strategic locations to allow remote entry of reel selection, PIN, job number, etc.
- Can be equipped with optional Serial Port Kit for use with an external reader.
- No limit for number of keypads in the system.
- Any reel dispense points can be opened from any keypad.

MODELS AVAILABLE	
<input type="checkbox"/> 3110-016	Keypad with Serial Port
TECHNICAL DATA	
Function	Module allows remote entry of PIN, job number, qty, etc.
Requirements & Limitations	Minimum 1 keypad required to operate a remote system No limit for number of keypads in the system
Power	Input - 24 V DC, output - 24 V DC

Description:

- 1.1. The standard keypads are designed to be located in strategic locations to allow remote entry of reel selection, PIN, job number, etc.
- 1.2. Can be equipped with optional Serial Port Kit for use with an external reader.
- 1.3. No limit for number of keypads in the system.
- 1.4. Any reel dispense points can be opened from any keypad.

Specifications

- 2.1. Synergy system will require a minimum of one keypad to operate a remote system
- 2.2. Synergy system keypad will have no limit to the number of keypads in the system
- 2.3. Synergy standard keypad will have an input of 24 VDC and an output of 24 VDC
- 2.4. Synergy can be equipped with a serial port kit for use with an external reader

Warranty

- 3.1. All Synergy components will have a 1-year parts, labor, and mileage warranty (defects in materials and workmanship only).