

Used Fluid Equipment Spillguard



Used Fluid

Overview

Spillguard drains capture used fluids and transfer to any bulk storage tank using a cam-lock kit and evacuation system

- Balcrank "wide track" 4" caster dolly set for easy maneuvering on any floor surface.
- All Steel cover, container, and base design
- Drainage bowl made from high strength poly to provide collapsible safety feature and to assist in preventing container failure when an object is lowered onto drainage bowl.
- Drain bowl prevents splattering and includes filter to keep debris from entering container and speed drainage.
- Tip resistant balanced design.
- High quality powder coating for corrosion resistance. Drains are offered in black for used fluid and green for used Anti-freeze (Glycol).
- Used oil drains will come with a 1" cam-lock nipple and dust cap.
- Used anti-freeze drains will come with a 3/4" cam-lock nipple and dust cap.

MODELS AVAILABLE	DESCRIPTION
<input type="checkbox"/> 4110-026	Spillguard used oil drain
<input type="checkbox"/> 4110-027	Spillguard used oil drain drumless
<input type="checkbox"/> 4110-028	Spillguard used anti-freeze (Glycol) drain
<input type="checkbox"/> 4110-029	Spillguard used anti-freeze (Glycol) drain drumless

TECHNICAL DATA	
Tank Capacity	16 gal (60.5 l)
Telescoping Range	0-27 in. (0-69 m)
Air Inlet (quick connect)	1/4" NPT
Fluid Outlet	Used oil 1" cam-lock nipple Used anti-freeze 3/4" cam-lock nipple
Wetted Materials	Zinc Plated Steel, Steel, Viton®, HDPE, and PVC
Service Bulletin	SB 4225