

Spillguard Drain Description

The Balcrank Spillguard Drains will capture used fluids and transfer to any bulk storage tank using a quick coupler and evacuation system.

Spillguard Drain Details

- 2.1. Drain will have Balcrank "wide track" 4" caster dolly set for easy maneuvering on any floor surface.
- 2.2. Drain will have an all Steel cover, container, and base design, made in USA.
- 2.3. Drain will have a drainage bowl to be made from high strength poly to provide collapsible safety feature, to assist in preventing container failure when object is lowered onto drainage bowl.
- 2.4. Drain bowl will prevent splattering and include filter to keep debris from entering container and speed drainage.
- 2.5. Drain will have a tip resistant balanced design.
- 2.6. Drain will have a fluid level gauge included.
- 2.7. Drain will be powder coated for corrosion resistance with high quality powder coating. Drains are offered in black for used oil and green for used antifreeze.

Spillguard Drain Models Available:

- 4110-026** Used Oil
- 4110-028** Anti-freeze
- 4110-027** Drumless Used Oil Drain
- 4110-029** Drumless Anti-freeze Drain

Spillguard Drain Specifications:

- 4.1. Drain will be 24" W x 55"H (61" H fully extended)
- 4.2. Drain will have bowl dimensions of 19.25" diameter
- 4.3. Drain will have a capacity of 16 gal (60.5 l)
- 4.4. Drain will have a telescoping range of 0-27 in. (0-69 m)
- 4.5. Drain will have fluid outlet of 3/4" NPT(M) for Anti-freeze and 1" NPT(M) for Used Oil

Materials:

- 5.1. The wetted materials will consist of Zinc-plated Steel, Steel, Viton, HDPE, and PVC

Warranty:

- 6.1. Drain will have a 1-year parts, labor, and mileage warranty (defects in materials and workmanship only)