## **Used Fluid Equipment Truck Drain**



## Cam-Lock Coupler & Nipple rated for vacuum or up to 3,000 psi (207 bar)

Cam-Lock Kits

4140-061 Cam-Lock Kit 1" for used oil for use with Pit Boss Bare 4140-020

Includes: Fluid Ball Valve, Cam-Lock nipple, Cap, and Hex nipple

4140-067 Cam-Lock Kit 3/4" for anti-freeze for use with Pit Boss Bare 4140-020

Includes: Fluid Ball Valve, Cam-Lock nipple, Cap, and Hex nipple

Hose Kit for waste oil evacuation



4140-013 Hose Kit for waste oil evacuation Includes: 4140-017 - Cam-lock coupler 1" x 1", 8181-002X - Hose low pressure 2.5' x 1"

## **Features**

The Truck Drain comes pre-assembled allowing for immediate use. Designed to capture used fluids. Includes "used oil only" and "used anti-freeze only" decals for fluid identification. Connects to a used oil evacuation system using a dry-break or cam-lock kit (sold separately) and evacuation system.

- Two fixed 8" wheels and one swivel caster on rear
- Double baffles with upper screen and a catch lip help prevent fluid from splashing out
- Tubular U-handle design for excellent maneuvering
- Powder coated for corrosion resistance with high quality powder coating. Drains are available in safety yellow.
- All Steel design

MODELS AVAILABLE		DESCRIPTION
	4120-006	Truck Drain Bare

TECHNICAL DATA		
MODELS	4120-006	
Tank Capacity	26 gal (98.4 l)	
Fluid Outlet	1"	
Measurements	9" H x 24" W x 36" L	
Wetted Materials	Zinc Plated Steel, Steel, Viton*, HDPE, and PVC	
Service Bulletin	SB 4051	