

CF Diaphragm Pump - Drum Packages



Overview

- Compact design mounting bracket.
- Heavy-duty cart - easily holds and rolls up to 55 gallon drum.
- Large semi-pneumatic tires - allows for easy maneuvering of cart.
- Large non-marking rear caster - built in break for safe and secure dispensing.

Includes

- 1120-025A, CF15 AODD Pump for DEF.
- 8570-006, 6' x 3/4" suction hose.
- 8561-012, 12' x 3/4" discharge hose.
- 4530-054, Drip tray.
- 4320-007, Drum cart 55 Gal for DEF.
- 4530-065, Side mount bracket.
- 3260-060, Filter Reg 1/4" auto drain, mini.

Options

- 3120-116, Meter DR style for DEF.
- 3340-012, Auto nozzle, stainless Steel.

MODELS AVAILABLE	DESCRIPTION
<input type="checkbox"/> 1210-054P	CF15 Non-metered, Manual Nozzle
<input type="checkbox"/> 1210-055P	CF15 Metered, Manual Nozzle
<input type="checkbox"/> 1210-056P	CF15 Non-metered, Auto Nozzle
<input type="checkbox"/> 1210-057P	CF15 Metered, Auto Nozzle

TECHNICAL DATA	
Air inlet	3/8" NPSM(F)
Fluid inlet port	1/2" BSPP(F) DEF
Fluid outlet port	1/2" BSPP(F) DEF
Max. Free Flow	14 gal/min (50 l/min)
Air pressure range	45-100 psi (3-7 bar)
Solids in suspension	1/8" (3 mm)
Wetted Materials	PTFE (Teflon®), Viton®, Polypropylene, Stainless Steel, Hytrel®
Recommended fluids	Diesel exhaust fluid
Recommended Applications	Fluid dispensing, transfer, evacuation and distribution systems
Service Bulletin	SB 1122