

CF Diaphragm Pump - Tote Packages



Overview

- Compact design mounting bracket

Includes

- 1120-025A, CF15 AODD Pump for DEF.
- 8570-006, 6' x 3/4" Suction hose.
- 8561-020, 20' x 3/4" Discharge hose.
- 4530-054, Drip tray.
- 4530-065, Side mount bracket.
- 3260-060, Reg 1/4" auto drain, mini.

Options

- 3120-116, Meter DR style for DEF.
- 3340-018, Manual nozzle, polyethylene- BSPP.

MODELS AVAILABLE	DESCRIPTION
<input type="checkbox"/> 1210-054	CF15 Non-metered, Manual Nozzle
<input type="checkbox"/> 1210-055	CF15 Metered, Manual Nozzle
<input type="checkbox"/> 1210-056	CF15 Non-metered, Auto Nozzle
<input type="checkbox"/> 1210-057	CF15 Metered, Auto Nozzle

TECHNICAL DATA	
Air inlet	3/8" NPSM(F)
Fluid inlet port	1/2" BSPP(F) DEF
Fluid outlet port	1/2" BSPP(F) DEF
Max. Free Flow	14 gal/min (50 l/min)
Air pressure range	45-100 psi (3-7 bar)
Solids in suspension	1/8" (3 mm)
Wetted Materials	PTFE (Teflon®), Viton®, Polypropylene, Stainless Steel, Hytrel®
Recommended fluids	Diesel exhaust fluid
Recommended Applications	Fluid dispensing, transfer, evacuation and distribution systems
Service Bulletin	SB 1122