

Tote Air Outfits Description

Balcrank Diesel Exhaust Fluid products will include pumps and outfits that could be placed in dealerships, garages, and gas stations. The Balcrank true blue Diesel Exhaust Fluid Systems will offer dispense options for all types of facilities. DEF tote air units will include AODD pump, hose, and dispense nozzle.

Tote Air Outfits Details

- 2.1. Tote Air Outfits will have an AODD 1/2" Poly pump.
- 2.2. Tote Air Outfits will be assembled and ready for use out of the box.
- 2.3. Tote Air Outfits Closed or Open coupler systems are NOT included in outfit – customer orders separately depending on fluid container requirements.

Tote Air Outfits Available:

- 1210-054** CF15 Non-metered, Manual Nozzle
- 1210-055** CF15 Metered, Manual Nozzle
- 1210-056** CF15 Non-metered, Auto Nozzle
- 1210-057** CF15 Metered, Auto Nozzle

Tote Air Outfits Specifications:

- 4.1. Tote Air Outfits will have a fluid inlet port of 1/2" BSPP (F)
- 4.2. Tote Air Outfits will have a fluid outlet port of 1/2" BSPP (F)
- 4.3. Tote Air Outfits will have an air inlet port of 3/8" BSPP (F)
- 4.4. Tote Air Outfits will have a free flow rate of 14 gal/m (50 l/min)
- 4.5. Tote Air Outfits will have an operating air pressure of 45-100 psi (3-7 bar)

Materials:

- 5.1. The wetted materials will consist of PTFE (Teflon), Viton, Polypropylene, Stainless Steel, Hytrel

Warranty:

- 6.1. Tote Air Outfits will have a 1-year replacement only warranty (defects in materials and workmanship only)