

Lion™ 350 Inductor Package Description

Lion™ 350 60:1 grease pump is used with 120 and 400 lb drums. The air operated pump hoist lifts and lowers the pump, making drum changes easier, faster and safer. The pumps lower end is rigidly fixed to a follower plate with a single rubber lip. The weight of the pump, pump bracket and follower plate plus atmospheric pressure push the assembly against the grease eliminating channeling and air pockets, keeping grease free from contaminants, minimizing waste and aiding pump priming.

Lion™ Inductor Package Models Available

- ❑ **1451-009** Package, Lion™ 350, 60:1 Inductor Includes:
1450-012 Lion™ 350, 60:1 Grease 120 lbs
4450-003 Inductor, Gravity, Pump Lift & follower plate
- ❑ **1451-008** Package, Lion™ 350, 60:1 Inductor Includes:
1450-011 Lion™ 350, 60:1 Grease 400 lbs
4450-003 Inductor, Gravity, Pump Lift & follower plate

Lion™ Inductor Package Specifications

- 3.1. Inductor package will have a 3" (75 mm) diameter of the pneumatic cylinder
- 3.2. Inductor package will have an air inlet of 1/2" NPT(M)
- 3.3. Inductor package will have an equipment height of 58" (1,470 mm) minimum to 94.5" maximum (2,400 mm)
- 3.4. Inductor package will have a stroke of 36.6" (930 mm) of the pneumatic cylinder

Warranty

- 4.1. The Lion™ 350 60:1 Inductor will have a 1-year standard warranty on defects in materials and workmanship only.