


Lion™ 450 - 40:1

Pumps
Piston



DIMENSIONS INCHES (MM)				
1450-002				
A	B	C	D	E
53.25" (1,357 mm)	19.75" (502 mm)	2" (50 mm)	33.5" (855 mm)	N/A
1450-003				
45.25" (1,152 mm)	19.75" (502 mm)	2" (50 mm)	25.5" (650 mm)	N/A
1450-004				
39" (992 mm)	19.75" (502 mm)	2" (50 mm)	19.25" (490 mm)	16.25" (410 mm)


Fluids

- Grease up to NLGI-2

Applications

- HD truck grease dispensing needing simultaneous dispense points
- Truck fleets fifth wheel applications
- Lube trucks
- Railroad/mass transit
- In-plant
- Marine

NLGI-2, 21 °C (70 °F) CAPACITY



Overview

Designed for medium volume applications that require higher flow and pressure delivery. This pump can be used with a follower plate system, combined with a gravity inductor system, or a double post RAM for simultaneous dispense, and higher flow applications.

MODELS AVAILABLE	DESCRIPTION
<input type="checkbox"/> 1450-003	Lion™ 450 40:1 grease 120 lb drum pump
<input type="checkbox"/> 1450-002	Lion™ 450 40:1 grease 400 lb drum pump
<input type="checkbox"/> 1450-004	Lion™ 450 40:1 grease bulk tote pump

TECHNICAL DATA	
Pump ratio	40:1
Continuous duty flow rate	8 lb/min (3.5 kg/min)
Cycles per lb	10
Maximum free flow	24 lb/min (11 kg/min)
Operating air pressure	30 - 200 psi (1.38- 14 bar)
Maximum fluid stall pressure	8,000 psi (560 bar)
Air motor effective diameter	4.5" (115 mm)
Air motor stroke	4" (100 mm)
Air consumption ⁽¹⁾	26.5 cfm (750 NI/min)
Air inlet	1/2" NPT(F)
Fluid outlet	1/2" NPT(F)
Wetted materials	Cast Iron, Steel, Hard chromed steel, UHMWPE, Buna-N™ and PTFE
Noise level ⁽²⁾	80 dB
Service Bulletin	SB 1131

(1) Air consumption at 5 bar air pressure, NLGI-0 grease at 20° C and 80 cpm.
 (2) Noise level measured at 1 m from the pump, 7 bar air pressure and free delivery.
Warning! Do not use any Lion™ 450/600 series products with flammable fluids.

Verify fluid compatibility with MSDS sheets.
 Contact Balc crank for pumping grease higher than NLGI-2 and specific system design performance technical data.