

CF10 Poly AODD Pump-CenterFlo Description

CenterFlo pumps can handle a wide range of fluids used for vehicle service.

Typical applications are transferring, dispensing, and evacuation, up to 10 gal/min. They can be used as stand-alone pumps for transfer applications.

CF10 Poly AODD Pump-CenterFlo Models Available

- 1120-029** CF10 Polypropylene
- 1120-034** CF10 Polypropylene / DEF

CF10 Poly AODD Pump-CenterFlo Specifications

- 3.1. AODD Pump will have a 1:1 ratio
- 3.2. AODD Pump will have an air inlet port of 3/8" NPSM(F)
- 3.3. AODD Pump will have a fluid inlet port of 1/2" NPT(F) 1120-029A & 1/2" BSPP(F) DEF 1120-034
- 3.4. AODD Pump will have a fluid outlet port of 1/2" NPT(F) 1120-029A & 1/2" BSPP(F) DEF 1120-034
- 3.5. AODD Pump will have a free flow of 10 gal/min (38 l/min) 100 psi (7 bar) air pressure
- 3.6. AODD Pump will have an operating air pressure of 22 to 102 psi (1.5 to 7 bar)
- 3.7. AODD Pump will have a maximum size of suspended solids of 1/8" (3 mm)

Materials

- 4.1. The wetted materials will consist of PTFE (Teflon[®]), Viton[®], Polypropylene, Stainless Steel, Acetal, and Hytrel[®]

Warranty

- 5.1. The CenterFlo AODD pump will have a 1-year standard warranty on defects in materials and workmanship only.