

### CF15 Poly/Mix AODD Pump-CenterFlo Description

CenterFlo pumps with a dual inlet for 1:1 ratio mixing of fluids with similar viscosities, like windshield wash or anti-freeze with water. All dual inlet pumps have 2 x 2 - 3/8" NPT(F) inlet ports.

### CF15 Poly/Mix AODD Pump-CenterFlo Models Available

- ☐ **1120-028A** CF15 Polypropylene Mixing

### CF15 Poly/Mix AODD Pump-CenterFlo Specifications

- 3.1. AODD Pump will have a 1:1 ratio
- 3.2. AODD Pump will have an air inlet port of 3/8" NPSM(F)
- 3.3. AODD Pump will have two fluid inlet ports of 2 - 3/8" NPT(F)
- 3.4. AODD Pump will have a fluid outlet port of 1/2" NPT(F) & flange
- 3.5. AODD Pump will have a free flow of 15 gal/min (50 l/min) based on 100 psi (7 bar) air pressure
- 3.6. AODD Pump will have an operating air pressure of 22 to 102 psi (1.5 to 7 bar)
- 3.7. AODD Pump will have a maximum size of suspended solids of 1/8" (3 mm)

### Materials

- 4.1. The wetted materials will consist of PTFE (Teflon), Viton, Polypropylene, Stainless Steel, Acetal, and Hytrel

### Warranty

- 5.1. The CenterFlo AODD pump will have a 1-year standard warranty on defects in materials and workmanship only.