

CF65 AODD Pump-CenterFlo Description

CenterFlo pumps can handle a wide range of fluids used for vehicle service.

Typical applications are high volume transferring, bulk fill, and evacuation up to 65 gal/min. They can be used as stand-alone pumps for transfer applications or as systems pumps that include hose reels.

CF65 AODD Pump-CenterFlo Models Available

- 1120-033** CF50 Aluminum
- 1120-039** CF50 Polypropylene

CF65 AODD Pump-CenterFlo Specifications

- 3.1. AODD Pump will have a 1:1 ratio
- 3.2. AODD Pump will have an air inlet port of 1/2" NPSM(F)
- 3.3. AODD Pump will have a fluid inlet port of 1 1/2" NPT(F) + ANSI flange B16.5 150 lb
- 3.4. AODD Pump will have a fluid outlet port of 1 1/2" NPT(F) + ANSI flange B16.5 150 lb
- 3.5. AODD Pump will have a free flow of 65 gal/min (250 l/mn) based on 100 psi (7 bar) air pressure
- 3.6. AODD Pump will have an operating air pressure of 22-102 psi (1.5-7 bar)
- 3.7. AODD Pump will have a maximum size of suspended solids of 1/4" (6 mm)

Materials

- 4.1. The wetted materials will consist of Aluminum, Acetal, Buna-N™, Stainless Steel

Warranty

- 5.1. The CenterFlo AODD pump will have a 1-year standard warranty on defects in materials and workmanship only.