

Control Handles - Water based Fluids



Fluids

- Anti-freeze (Glycol)
- Windshield wash solution
- Water

Markets Served

- Car and truck dealers
- Fast lube and maintenance shops
- Fleets

Overview

- Reinforced polyamide body and stainless Steel valve mechanism.
- Ergonomic-grip.
- Includes Brass inlet swivel 1/2" NPT(F), flex-90 extension and a 1/4 turn manual tip.

MODELS AVAILABLE	EXTENSION TYPE & NOZZLE	EXTENSION CODE
<input type="checkbox"/> 3320-055	Flex 90 1/4 turn - oil	3332-102
<input type="checkbox"/> 3330-201	Metered - Flex 90 1/4 turn - oil	3332-102

TECHNICAL DATA

	NON METERED	METERED
Units of measure	-	Batch: Quarts, Pints, Gallons and Liters (in 0.01 increments)
Accuracy	-	+/- 0.5% of reading (lubricating oils)
Flow Rate	8 gal/min (30 l/min)	
Maximum pressure	725 psi (50 bar)	
Swivel Inlet	1/2" NPT(F)	
Dispense Nozzle OD	Manual 1/4 turn for OIL = 0.705"	
Operating Temperature	122 °F (50 °C)	
Weight	1 lb (0.4 kg)	2.2 lb (1 kg)
Compatible Fluids	Anti-freeze, windshield wash solution, and water	
Wetted Materials	Fiberglass reinforced thermoplastic, polyurethane rubber, and brass	Fiberglass reinforced thermoplastic, polyurethane rubber, Viton®, brass, and stainless steel
Service Bulletin	SB 3105	