


Grease Piston Pumps LYNX® 55:1 Pumps

1



DIMENSIONS INCHES (MM)				
1150-022				
A	B	C	D	E
24.40" (620 mm)	8" (202 mm)	1" (26 mm)	1.56" (40 mm)	16.5" (418 mm)
1150-023				
36.62" (930 mm)	8" (202 mm)	1" (26 mm)	1.56" (40 mm)	28.65" (728 mm)
1150-024				
44.12" (1120 mm)	8" (202 mm)	1" (26 mm)	1.56" (40 mm)	36.14" (918 mm)

TECHNICAL DATA	
Pump ratio	55:1
Continuous duty free flow	7 lbs/min
Cycles per lb @ 100 psi (7 bar) free flow	318
Pump delivery, 100 psi (7 bar) air pressure and free flow	0.70 lb/min (0.32 kg/min)
Operating air pressure range	20-140 psi (1.5-10 bar)
Max fluid stall pressure @ 140 psi (10 bar) air	7,700 psi (550 bar)
Effective Air Piston Diameter	2.75" (70 mm)
Air motor stroke	1.5" (38 mm)
Air consumption 90 psi (6 bar) & 110 cycles per minute	5.8 SCFM
Air inlet	1/4" NPT(F)
Fluid outlet	1/4" NPT(F)
Wetted materials	Steel, Zinc, Aluminum, Buna-N™, PTFE (Teflon)
Noise	92 dB
Service Bulletin	SB 1116

Warning! Do not use any LYNX® series products with flammable fluids.

Verify fluid compatibility with MSDS sheets.

Contact Balcrank for pumping grease higher than NLGI-2 and specific system design performance technical data.

Fluids & Applications

Designed for 25-35, 120, and 400 lb. drums, portable use, and single point dispense. Ideal for the low volume user for grease fittings on smaller vehicles. LYNX® grease pumps are double acting positive displacement capable of delivering up to 1.2 lbs. (.54 kg) per minute.

Fluids

- Grease up to NLGI-2

Applications

- Roll-around unit for small vehicle grease points
- Agriculture/farm implements
- Small auto/truck shops
- Tire & transmission shops
- In-plant low volume use

MODELS AVAILABLE	DESCRIPTION
1150-022	LYNX® 55:1 Grease 25-35 lbs
1150-023	LYNX® 55:1 Grease 120 lbs
1150-024	LYNX® 55:1 Grease 400 lbs

