Control Handles DR Meter (Digital Register Meter)






See Dispense nozzle OD for important details

| TECHNICAL DATA | | |
|---|--|--|
| Units of measure | Batch: Gallons, Quarts, Pints, and Liters (in 0.01 increments) | |
| Accuracy | +/- 0.5% of reading (lubricating oils) | |
| Flow Range | 0.26-8 gal/min (1-30 l/min) | |
| Maximum pressure | 1,450 psi (100 bar) | |
| Swivel inlet | 1/2" NPT(F) | |
| Dispense Nozzle OD | Auto = 0.605" Manual 1/4 turn for OIL = 0.705" Manual 1/4 turn for ATF= 0.315" Verify ID of ATF fill port for compatibility | |
| Operating temperature 14° F to 140° F (-10° C to 60° C) | | |
| Weight | 4 lb (1.80 kg) | |
| Battery | 2 x 1.5 v alkaline "AAA" | |
| Compatible Fluids | Oil, transmission fluid, hydraulic fluid, and anti-freeze | |
| Wetted Materials | Liquid Crystal Polymer (LCP), aluminum, Buna-N™, zinc plated steel, stainless steel, neodymium, and brass | |
| Service Bulletin | SB 3095 | |

Dimensions inches (mm)





Synthetic and mineral based lubricants Gear Oil Hydraulic oil and fluids ATF Anti-freeze (Glycol) and anti-freeze water solution

- Sealed battery compartment; 2 AAA batteries
- Precision robotically machined aluminum die-cast fluid chamber for repeatable accuracy
- Low power consumption with auto sleep function
- Trip mode function; can operate as a simple fluid management device
- Non-resettable totalizer; maintains total volume of meter since day one
- Ergonomic comfort handle
- Unique 1/4 turn manual tip; fast, simple
- Flanged coupling; prevents leaks commonly found in competitive meters
- Swivel protective cover
- Affordable repairability

Markets Served

- Car and truck dealers
- Fast lube and maintenance shops
- Fleets
- Mining and construction
- Lube trucks

| MODELS AVAILABLE | EXTENSION Type & Nozzle | EXTENSION CODE | |
|---|-------------------------------|----------------|--|
| Verify ID of ATF fill port for compatibility. | | | |
| 3330-161 | Flex Auto | 3332-095 | |
| 3330-157 | Rigid 1/4 turn - OIL | 3332-091 | |
| 3330-158 | Flex 90 1/4 turn - OIL | 3332-092 | |
| 3330-159 | Flex-memory 1/4 turn - OIL | 3332-093 | |
| 3330-169 | Rigid 1/4 turn - ATF | 3332-101 | |
| 3330-172 | Flex-memory 1/4 turn - ATF | 3332-104 | |
| 3330-166 | DR bare | - | |