## Control Handles EP Meter (Electronic Preset Meter)






TECHNICAL DATA		
Units of measure	Quarts, pints, gallons, liters	
Accuracy	+/- 0.5 %	
Flow Range	0.25-7.5 gal/m (1-30 l/m)	
Maximum pressure	1,425 psi (100 bar)	
Swivel Inlet	1/2" NPT(F)	
Battery	4 x alkaline "AA"	
Weight	3.7 lb (1.7 kg)	
Compatible Fluids	Oil, transmission fluid, hydraulic fluid, anti-freeze and gear oil	
Wetted Materials	Aluminum, AISI316 Stainless Steel, Buna-N™; Delrin, Brass, and Zinc Plated Steel	
Service Bulletin	SB 3115	

\*Patent pending

Dimensions in (mm)



## Synthetic and mineral based lubricants Gear oil Hydraulic fluids ATF

Preset dispensing allows hands-free operation as the meter automatically shuts off once the desired preset amount is reached.

- Programmable for quarts, pints, gallons, liters
- Save up to 10 preset values in built-in memory
- Operates in manual or automatic preset
  mode
- Transaction memory: Stores volume delivered of the last 5 transactions
- Low battery indicator

## **Markets Served**

- Auto and truck dealerships
- Truck fast lube and maintenance shops
- Fleets
- Mining and construction
- · Railroad and mass transit

MODELS Available	EXTENSION TYPE & Nozzle	EXTENSION CODE
3331-031	Rigid 1/4 turn - OIL	3332-091
3331-032	Flex Memory - OIL	3332-093
3331-033	DR bare	-