Lightweight Double Wall Oil Dispense Piston Pump



Package includes

- Double wall tank choice of 165 gal (L 29" x W 28" x H 61"),
 275 gal (L 43" x W 28" x H 61"), or 400 gal (L 64" x W 30" x H 68")
- Hose reel choice of Evolution or Classic series hose reel, 30' or 50'x 1/2"
- Piston pump choice of LYNX® 3:1, LYNX® 5:1 HD, or Panther® 3:1
- DR handle w/flex-m ext. & 1/4 turn manual tip for oil
- F/R auto drain 1/4" NPT(F)
- 2.5' reel inlet hose
- 5' air connecting hose
- Air quick connect coupler & nipple
- Sight gauge
- Vented fill cap
- Pump & reel bracket

(See additional tank accessories on pg. 152)

*As with all tanks, be sure to follow local and state guidelines for tank placement and installation. Some cities and counties have not approved the UL 2258 certification, as it is different that the familiar UL142 that pertains to steel tanks, so be sure to check with your local Fire Marshal and/or city and county regulations before ordering.



Light Duty Applications

· Low volume, small service centers

MODELS Available	DESCRIPTION
1135-004	50' EVO Reel, LYNX® 3:1 pump, 165 gal
1135-013	30' EVO Reel, LYNX° 3:1 pump, 275 gal
1135-016	50' EVO Reel, LYNX® 3:1 pump, 275 gal
1135-019	30' Classic Reel, LYNX® 3:1 pump, 275 gal
1135-022	50' Classic Reel, LYNX® 3:1 pump, 275 gal
1135-028*	50' EVO Reel, LYNX® 3:1 pump, 400 gal
1135-034*	50' Classic Reel, LYNX° 3:1 pump, 400 gal



Medium Duty Applications

Low to medium volume, small service centers

MODELS Available	DESCRIPTION
1135-011	50' Classic Reel, LYNX° 5:1 HD pump, 165 gal
1135-014	30' EVO Reel, LYNX° 5:1 HD pump, 275 gal
1135-017	50' EVO Reel, LYNX° 5:1 HD pump, 275 gal
1135-020	30' Classic Reel, LYNX° 5:1 HD pump, 275 gal
1135-023	50' Classic Reel, LYNX® 5:1 HD pump, 275 gal
1135-029*	50' EVO Reel, LYNX° 5:1 HD pump, 400 gal
1135-035*	50' Classic Reel, LYNX® 5:1 HD pump, 400 gal



These double wall tanks feature:

- Inner tank made of blow-molded, highdensity, seamless polyethylene that is leakproof and will never corrode
- Outer tank is made of weld-free galvanized steel and roll seamed with an oil and fire-resistant seal
- Outer tank holds 110 percent of inner tank for maximum protection
- Extremely light, up to 50 percent lighter than conventional steel tanks
- Can be used for DEF, diesel and bio fuels, motor oil, and ATF
- Compact, economical design (8 sq. ft. for 1000 l)
- Wide handles on each end allow for easy handling and transportation
- UL 2258 certified*
- 4 x 2" bung openings
- · All tanks ship assembled



Medium/Heavy Duty Applications

• Medium volume service centers

MODELS Available	DESCRIPTION
1135-006	50' EVO Reel, Panther® 3:1 pump, 165 gal
1135-009	30' Classic Reel, Panther® 3:1 pump, 165 gal
1135-012	50' Classic Reel, Panther® 3:1 pump, 165 gal
1135-018	50' EVO Reel, Panther® 3:1 pump, 275 gal
1135-021	30' Classic Reel, Panther® 3:1 pump, 275 gal
1135-024	50' Classic Reel, Panther® 3:1 pump, 275 gal
1135-030*	50' EVO Reel, Panther® 3:1 pump, 400 gal
1135-036*	50' Classic Reel, Panther® 3:1 pump, 400 gal

^{*165} gallon and 275 gallon ship assembled. 400 gallon ship equipment and tank separately