

Fluid Inventory Control Nex-U® U-count & U-view

U-count fluid control module includes a high visibility LED display and the software required to function with the rest of the NEX-U® system components.



3110-135



3110-134

U-COUNT	3110-135
Description	Fluid meter and solenoid valve controller includes Bluetooth®, CAN BUS communications.
Service Bulletin	SB 3805

U-VIEW	3110-134
Description	U-view remote display module
Service Bulletin	SB 3804

U-count

The U-count allows the use of external solenoid/meter combination to control almost any fluid:

- DEF
- Highflow Oil
- Grease
- WW Fluid
- Anti-freeze

U-view

U-view requires hard-wired connection (data and power) to a U-dat keypad or to a 110 - 240 V AC power supply using a 24 V DC external transformer (U-power or U-power*).

Ucount Uview

Features

U-count fluid control module includes a high visibility LED display and the software required to function with the rest of the NEX-U® system components.

The LED display shows the number assigned in the system and four different LED lights show the operation of the valve for diagnosis and two buttons for system configuration. U-count supports CAN BUS hard-wired communication that transmits data and power required to open the solenoid valve, for data communication with other system components and Bluetooth® to communicate with a U-vision or U-vision+ handle.

U-view has remote, high visibility, LED display that shows the volume delivered through various U-valves (no simultaneous operation supported). U-view supports Wi-Fi® and hardwired communication.

MODEL AVAILABLE	
3110-135	U-count meter, solenoid, bluetooth
3110-134	U-view remote display module