

AODD Electric Pumps



1200-020



1200-021

Fluids & Applications

Electric diaphragm pump is designed for simple and efficient transfer of anti-freeze, windshield wash solution and diesel exhaust fluid (DEF). Accommodates any system.

Fluids

- Anti-freeze (Glycol)
- Windshield wash solution
- DEF

Markets Served

- Car and truck dealers
- Fleets
- Mining and construction
- Railroad and mass transit vehicles
- In-plant transfer
- Lube trucks
- Quick lubes

TECHNICAL DATA		
	1200-020	1200-021
Fluid inlet port	1" BSPP(M)	1" BSPP(M)
Fluid outlet port	1" BSPP(M)	1" BSPP(M)
Flow Rate	8.5 gal/min (32.18 l/min)	9.5 gal/min (34.07 l/min)
Working Pressure	23 psi (1.6 bar)	23 psi (1.6 bar)
Power	120 V AC, UL approved	12 V DC, UL approved
Wetted Materials	Stainless Steel, Viton®, PPE	Stainless Steel, Viton®, PPE
Service Bulletin	SB 1129	SB 1130

MODELS AVAILABLE	DESCRIPTION
1200-020	120 V AC Diaphragm pump, UL auto shut-off
1200-021	12 V DC Diaphragm pump, UL auto shut-off

** Balcrank does not recommend pumping windshield wash or any other fluid below 100° flash point. Contact Balcrank for additional information.