

Closed Systems Drum Packages Electric Diaphragm Pump



Features

- Compact design mounting bracket
- Heavy-duty cart - easily holds and rolls up to 55 gallon drum
- Large semi-pneumatic tires - allow for easy maneuvering of cart
- Large non-marking rear caster - built in break for safe and secure dispensing

Includes:

- 8570-006 6' x 3/4" Suction hose
- 8561-012 12' x 3/4" Discharge hose
- 4530-054 Drip tray
- 4320-014 Drum cart 55 gal for DEF
- 4530-065 Side mount bracket

Options:

- 3120-116 Meter DR style for DEF
- 1200-020 120 V AC Electric diaphragm pump
- 1200-021 12 V DC Electric diaphragm pump
- 3340-012 Auto nozzle, stainless steel
- 3340-015 Manual nozzle, polyethylene

Pump includes automatic shutoff.

Pump is UL approved

TECHNICAL DATA

	DATA 120 V AC (1200-020)	DATA 12 V DC (1200-021)
Max. Free Flow	8.5 GPM	9.5 GPM
Working Pressure	23 psi (1.6 bar)	23 psi (1.6 bar)
Power	120 V AC	12 V DC
Wetted Materials (pump)	Stainless Steel, Viton, PPE	Stainless Steel, Viton, PPE
Service Bulletin	SB 1129	SB 1130

MODELS AVAILABLE	DESCRIPTION
1210-046P	120 V AC Non-metered, Manual Nozzle
1210-048P	120 V AC Non-metered, Auto Nozzle
1210-049P	120 V AC Metered, Auto Nozzle
1210-053P	12 V DC Metered, Auto Nozzle

CLOSED system containers have a valve coupling system that seals the container opening on drums and totes (IBC) to prevent dirt, debris, bugs, etc., from entering the container and contaminating the diesel exhaust fluid. Liquid in container system is sealed and secure, throughout container life cycle.

DEF Packages do not include coupler systems. Order Separately.

You must choose a coupler kit to create a complete system for your distribution needs.

For closed systems, use Reusable Poly Valve (RPV) or Reusable Stainless Valve (RSV) systems accessories. RSV and RPV components are interchangeable.