

## Closed Systems Drum Packages CF Diaphragm Pump



### Features

- Compact design mounting bracket
- Heavy-duty cart - easily holds and rolls up to 55 gallon drum
- Large semi-pneumatic tires - allows for easy maneuvering of cart
- Large non-marking rear caster - built in break for safe and secure dispensing

#### Includes

- 1120-025A CF15 AODD Pump for DEF
- 8570-006 6' x 3/4" suction hose
- 8561-012 12' x 3/4" discharge hose
- 4530-054 Drip tray
- 4320-014 Drum cart 55 Gal for DEF
- 4530-065 Side mount bracket
- 3260-060 Filter Reg 1/4" auto drain, mini

#### Options

- 3120-116 Meter DR style for DEF
- 3340-012 Auto nozzle, stainless steel

MODELS AVAILABLE	DESCRIPTION
1210-054P	CF15 Non-metered, Manual Nozzle
1210-055P	CF15 Metered, Manual Nozzle
1210-056P	CF15 Non-metered, Auto Nozzle
1210-057P	CF15 Metered, Auto Nozzle

### TECHNICAL DATA

Air inlet	3/8" NPSM(F)
Fluid inlet port	1/2" BSPP(F) DEF
Fluid outlet port	1/2" BSPP(F) DEF
Max. Free Flow	14 gal/min (50 l/min)
Air pressure range	45-100 psi (3-7 bar)
Solids in suspension	1/8" (3 mm)
Wetted Materials	PTFE (Teflon) , Viton <sup>®</sup> , Polypropylene, Stainless Steel, Hytrel <sup>®</sup>
Recommended fluids	Diesel exhaust fluid
Recommended Applications	Fluid dispensing, transfer, evacuation and distribution systems
Service Bulletin	SB 1145

**CLOSED system** containers have a valve coupling system that seals the container opening on drums and totes (IBC) to prevent dirt, debris, bugs, etc., from entering the container and contaminating the diesel exhaust fluid. Liquid in container system is sealed and secure, throughout container life cycle.

Note: Pump packages include all hoses and adapters required for connecting a DEF pump to the air supply and DEF dispense line.

**DEF Packages do not include coupler systems.**

**You must choose a coupler kit to create a complete system for your distribution needs.**

**For closed systems, use Reusable Poly Valve (RPV) or Reusable Stainless Valve (RSV) systems accessories. RSV and RPV components are interchangeable.**