

## System Components Meters and Nozzles

METERS AND SOLENOIDS						
	MODEL	DESCRIPTION	INLET/OUTLET PORT	FLOW RATE	OPERATING PRESSURE	POWER
	3120-116	DR Style Meter for DEF	1/2" BSPP(F/F) & flange	0.25 - 13.2 gal/min (1 - 50 l/min)	435 psi (30 bar)	2 x 1.5 V alkaline batteries size "AAA"
	3120-119	DEF Turbine Meter	1" BSPP(M/M)	1.3-26.4 gal/min (4.92-99.94 l/min)	145 psi (10 bar)	2 x 1.5 V alkaline batteries size "AAA"
	3120-206	Turbine Meter, pulse-out	1" BSPP(F/F)	83 PPQ	145 psi (10 bar)	24 V AC
	3120-207	Solenoid	3/4" NPT(F/F)	8.4 gal/min (32.71 l/min)	150 psi (10 bar)	24 V AC
NOZZLES						
	MODEL	DESCRIPTION				
	3340-011	Nozzle, manual Polyethylene 3/4" barb (M)				
	3340-018	Nozzle, manual Polyethylene 3/4" BSPP(F)				
	3340-015	Nozzle, manual Polyethylene 1" barb (M)				
	3340-012	Nozzle, automatic shut-off Stainless steel, 3/4" BSPP(F)				
	3340-017	Nozzle, Magnetic, 3/4" BSPP(F)				
	4530-054	Nozzle holder, drip tray				