

## Fittings

HEX NIPPLES STANDARD & REDUCING			
	MODEL	NPT(M X M)	TECHNICAL DATA
	3270-091	1/2" x 3/8"	Steel 3,000 psi (207 bar)
	3270-043	1/2" x 1/2"	Brass 1,000 psi (68.9 bar)
	3270-095	3/4" x 3/8"	Steel 3,000 psi (207 bar)
	3270-092	3/4" x 1/2"	Steel 3,000 psi (207 bar)
	3270-044	3/4" x 3/4"	Brass 1,000 psi (68.9 bar)
	3270-096	1" x 3/4"	Steel 3,000 psi (207 bar)
	3270-045	1" x 1"	Steel 3,000 psi (207 bar)
SQUARE HEADED PLUG			
	MODEL	NPT(M)	TECHNICAL DATA
	3270-150	1/8"	Black Iron 2,000 psi (137.8 bar)
	3270-151	1/4"	Steel 3,000 psi (207 bar)
	3270-152	3/8"	Steel 3,000 psi (207 bar)
	3270-153	1/2"	Steel 3,000 psi (207 bar)
	3270-154	3/4"	Steel 3,000 psi (207 bar)
	3270-155	1"	Steel 3,000 psi (207 bar)
3270-156	2"	Steel 3,000 psi (207 bar)	
STREET ELBOW			
	MODEL	NPT(F X M)	TECHNICAL DATA
	3270-157	1/4" x 1/4"	Steel 3,000 psi (207 bar)
	3270-083	3/8" x 3/8"	Steel 3,000 psi (207 bar)
	3270-158	1/2" x 1/2"	Steel 3,000 psi (207 bar)
3270-159	3/4" x 3/4"	Steel 3,000 psi (207 bar)	
SWIVEL UNIONS 45°			
	MODEL	NPT(M) X NPS(F)	TECHNICAL DATA
	3270-066	1/2" x 1/2"	Steel 3,500 psi (241.13 bar)
	3270-062	3/4" x 3/4"	Steel 2,000 psi (137.8 bar)
3270-061	1" x 1"	Steel 2,000 psi (137.8 bar)	
SWIVEL UNIONS RIGID			
	MODEL	NPT(M) X NPS(F)	TECHNICAL DATA
	3270-097	1/8" x 1/4"	Steel 3,000 psi (207 bar)
	3270-025	1/4" x 1/4"	Steel 5,000 psi (344.7 bar)
	3270-098	1/4" x 3/8"	Steel 3,000 psi (207 bar)
	3270-050	3/8" x 3/8"	Steel 3,000 psi (207 bar)
	3270-046	3/8" x 1/2"	Steel 3,000 psi (207 bar)
3270-028	1/2" x 3/8"	Steel 3,000 psi (207 bar)	