



High Flow Control Handle

Model 3320-050High Flow Control Handle - Oil

IMPORTANT

Read these safety warnings and instructions in this manual completely, before installation and start-up of the control handle. It is the responsibility of the purchaser to retain this manual for reference. Failure to comply with the recommendations stated in this manual will damage the control handle and void factory warranty.

WARNING

Airborne particles and loud noise hazards.

Wear ear and eye protection.

WARNING

Before doing any maintenance on the control handle, be certain all pressure is completely vented from the pump, suction, discharge, piping, and all other openings and connections. Be certain the air supply is locked out or made non-operational, so that it cannot be started while work is being done on the control handle. Be certain that approved eye protection and protective clothing are worn at all times in the vicinity of the control handle. Failure to follow these recommendations may result in serious injury or death.

WARNING

DANGER: Not for use with fluids that have a flash point below 100°F (38°C). Examples: gasoline, alcohol. Sparking could result in an explosion which could result in death.



PRODUCT DESCRIPTION

The 3320-050 High Flow Control Handle is designed for service where larger volume deliveries are required. Features include a semi-automatic tip and a trigger lock.

SPECIFICATIONS

Max Flow Rate	16.4 gpm
Max Operating Pressure	1500 psi
Min Opening Pressure (Tip)	40 psi
Swivel Inlet	3/4" NPT
Wetted parts	Aluminum, Carbon Steel, Brass, NBR
Fluid Compatibility*	Engine Oil, Diesel Oil, ATF, Antifreeze, Gear Oil
Weight	4 lbs.
Dimensions	19.5" L x 5" W x 1.5" H

*Maximum viscosity SAE 140

CAUTION

Maximum Fluid Pressure 1500 PSI. Under no circumstances should the control handle be aimed at any person or your own body at anytime. Personal injury may result.

Thoroughly read and understand this manual before installing, operating or servicing this equipment.

**For Warranty Information Visit:
www.balcrank.com**

Balcrank® Corporation
Weaverville, NC 28787
800-747-5300
800-763-0840 Fax
www.balcrank.com

Revision Log:

Rev. A - Release

SERVICE BULLETIN SB3087
Rev. A 10/12