

CF30 AODD Pump-CenterFlo Description

CenterFlo pumps can handle a wide range of fluids used for vehicle service.

Typical applications are transferring, dispensing, and evacuation up to 28 gal/min. They can be used as stand-alone pumps for transfer applications or as systems pumps that include hose reels.

CF30 AODD Pump-CenterFlo Models Available

- 1120-026A** CF30 Polypropylene
- 1120-040** CF30 Aluminum
- 1120-031A** CF30 Polypropylene / DEF

CF30 AODD Pump-CenterFlo Specifications

- 3.1. AODD Pump will have a 1:1 ratio
- 3.2. AODD Pump will have an air inlet port of 3/8" NPSM(F)
- 3.3. AODD Pump will have a fluid inlet port of 1" NPT(F) for pumps 1120-026A and 1120-024
- 3.4. AODD Pump will have a fluid inlet port of 1" BSPP(F) for DEF pump 1120-031A
- 3.5. AODD Pump will have a fluid outlet port of 1" NPT(F) for pumps 1120-026A, 1120-024
- 3.6. AODD Pump will have a fluid outlet port of 1" BSPP(F) for DEF pump 1120-031A
- 3.7. AODD Pump will have a free flow of 28 gal/min (106 l/min) based on 100 psi (7 bar) air pressure
- 3.8. AODD Pump will have an operating air pressure of 22 to 102 psi (1.5 to 7 bar)
- 3.9. AODD Pump will have a maximum size of suspended solids of 3/16" (4 mm)

Materials

The wetted materials will consist of

- 4.1. 1120-026A and 1120-031A PTFE (Teflon) Viton, Polypropylene, Stainless Steel, and Hytrel
- 4.2. 1120-024 Aluminum, Acetal Teflon, Buna-N™, Stainless Steel, and Hytrel

Warranty

- 5.1. The CenterFlo AODD pump will have a 1-year standard warranty on defects in materials and workmanship only.