

Control Handles

Product Selection Matrix

UNIT OF MEASURE	FLOW RANGE	MAX. PRESSURE	WEIGHT	RECOMMENDED FLUIDS
NON-METERED				
-	0.26 - 10.5 gal/min (1-40 l/min)	1,450 psi (100 bar)	3.30 lb (1.5 kg)	Oil, transmission fluid, hydraulic fluid, and anti-freeze
DR SERIES METERED				
gallon, quart, pint, liter	0.26 - 8 gal/min (1-30 l/min)	1,450 psi (100 bar)	4 lb (1.80 kg)	Oil, transmission fluid, hydraulic fluid, and anti-freeze
MO SERIES METERED				
quart, liter	0.26 - 8 gal/min (1-30 l/min)	1,000 psi (70 bar)	4 lb (1.80 kg)	Oil, transmission fluid, hydraulic fluid, and anti-freeze
MR SERIES METERED				
quart, liter	0.26 - 8 gal/min (1-30 l/min)	1,450 psi (100 bar)	3.75 lb (1.7 kg)	Oil, transmission fluid, hydraulic fluid, and anti-freeze
MR SERIES PRESET METERED				
gallon, quart, liter	0.25 - 8 gal/min (1-30 l/min)	1,450 psi (100 bar)	4.4 lb (2 kg)	Oil, transmission fluid, hydraulic fluid, and anti-freeze
HIGHFLO NON-METERED				
-	0.26 - 24 gal/min (1- 90 l/min)	1,450 psi (100 bar)	4.5 lb (2.05 kg)	Oil, transmission fluid, hydraulic fluid, and anti-freeze
HIGHFLO METERED				
gallon, quart, pint, liter	0.52 - 19 gal/min (2-70 l/min)	1,450 psi (100 bar)	6.3 lb (2.85 kg)	Oil, transmission fluid, hydraulic fluid, and anti-freeze
ELECTRONIC PRESET METERED				
gallon, quart, pint liter	0.2 - 8 gal/min (0.8- 30 l/min)	1,425 psi (100 bar)	3.7 lb (1.7 kg)	Oil, transmission fluid, hydraulic fluid, and anti-freeze
BFH2 FLUID HANDLE NON- METERED				
-	8 gal/min (30 l/min)	725 psi (50 bar)	0.63 lb (284 kg)	DEF, windshield wash solutions, glycol, and anti-freeze
BFH2 FLUID HANDLE METERED				
gallon, quart, pint, liter	8 gal/min (30 l/min)	435 psi (30 bar)	1.81 lb (819 kg)	DEF, windshield wash solutions, glycol, and anti-freeze



DR SERIES



**MO SERIES
METERED**



**MR SERIES
METERED**



**MR SERIES
PRESET METERED**



**HIGHFLO
SERIES**



**ELECTRONIC
PRESET METERED**



**BFH2 METERED
SERIES**