

# Fluid Inventory Control Pump Sentinel

## Pump Sentinel Description:

- 1.1. Prevents theft by disabling up to six pumps
- 1.2. Safety shut-off at the end of the day; in case of component failure that could result in leaks and spills
- 1.3. Master key needed to turn system on
- 1.4. Includes a six-foot wiring harness
- 1.5. Small Console footprint: 6.5" L x 5" W x 3" H

Prevents fluid spills during non-working hours by using a built-in timer to turn off air supply to all pumps at a predetermined time each day.

## Pump Sentinel Specifications

- 2.1. The Pump Sentinel prevents fluid spills during non-working hours by using a built-in timer to turn off air supply to all pumps at a predetermined time each day.
- 2.2. The Pump Sentinel requires 120 VAC, 60/50 Hz, 50 Watts-output 24 VAC
- 2.3. The Pump Sentinel's control capacity is 6 products
- 2.4. The Pump Sentinel will have an operating temperature of 0° - 140° F (-17° - 60° C)
- 2.5. The Pump Sentinel will have an Solenoid rating of 24 VDC, 5 Watts Max.
- 2.6. The Pump Sentinel will have a dimension of 3" H x 6.5" W x 5" D
- 2.7. The Pump Sentinel will a cable length of 6ft.

## Warranty

- 3.1. All Pump Sentinel components will have a 1-year parts, labor, and mileage warranty (defects in materials and workmanship only).