

Portable Air Outfits Description

Balcrank Diesel Exhaust Fluid products will include pumps and outfits that could be placed in dealerships, garages, and gas stations. The Balcrank true blue Diesel Exhaust Fluid Systems will offer dispense options for all types of facilities. DEF portable air units will include portable drum cart, AODD pump, hose, and dispense nozzle.

Portable Air Outfits Details

- 2.1. Portable Air Outfits will have 8" diameter non-marking locking caster with a built-in break on rear of cart for safe and secure dispensing.
- 2.2. Portable Air Outfits will have 12" diameter semi-pneumatic tires for easy maneuvering.
- 2.3. Portable Air Outfits will have a heavy-duty cart, which easily holds and rolls a 55-gallon drum.
- 2.4. Portable Air Outfits will have an AODD 1/2" Poly pump.
- 2.5. Portable Air Outfits will be assembled and ready for use out of the box.
- 2.6. Portable Air Outfits Closed or Open coupler systems are NOT included in outfit – customer orders separately depending on fluid container requirements.

Portable Air Outfits Available:

- ☐ **1210-054P** CF15 Non-metered, Manual Nozzle
- ☐ **1210-056P** CF15 Non-metered, Auto Nozzle
- ☐ **1210-057P** CF15 Metered, Auto Nozzle

Portable Air Outfits Specifications:

- 4.1. Portable Air Outfits will have a fluid inlet port of 1/2" BSPP (F)
- 4.2. Portable Air Outfits will have a fluid outlet port of 1/2" BSPP (F)
- 4.3. Portable Air Outfits will have an air inlet port of 3/8" BSPP (F)
- 4.4. Portable Air Outfits will have a free flow rate of 14 gal/min (50 l/min)
- 4.5. Portable Air Outfits will have an operating air pressure of 45-100 psi (3-7 bar)

Materials:

- 5.1. The wetted materials will consist of PTFE (Teflon®), Viton®, Polypropylene, Stainless Steel, Hytrel®

Warranty:

- 6.1. Portable Air Outfits will have a 1-year replacement only warranty (defects in materials and workmanship only)