

# Used Fluid Equipment

## Roughneck II™

The Roughneck II™ drain captures used fluids and transfers them to any bulk storage tank. The unit uses regular shop air and can be pressurized to allow for self-evacuating.



## Features

- Patented automatic fluid evacuation valve eliminates gravity draining, pouring, or the need for an evacuation pump, **made in the USA**
  - 23 gallon storage tank; fewer drain intervals
  - A low pressure safety valve prevents over pressurization of tank.
  - Clear evacuation hose; provides fast fluid evacuation and shows fluid levels in tank.
- Includes:**
- 19.25" diameter catch basin that features an inlet strainer and s-hooks for tools
  - Splashguard bowl design prevents splattering, speeds drainage
  - Fully adjustable bowl height from 45" to 72"
  - One hand operation. No ball valves required for evacuation of fluid
  - Roughneck outlet tube mounts securely into bulk used fluid reservoir
  - 7' evacuation tube provides sight gauge for fluid level
  - Tank handle makes maneuvering easy.
  - Heavy gauge, all-steel construction guarantees long life
  - Tip-resistant balanced design
  - Large diameter rear rubber wheels and non-marking wide front casters maneuver the toughest shop floors

### TECHNICAL DATA

Air Pressure Operating Range	5-25 psi (.34-1.72 bar)
Tank Capacity	23 gal (87 l)
Telescoping Range	45"-72" (1.14-1.83 m)
Maximum Pressure	25 psi (1.72 bar)
Pressure Relief Valve	30 psi (2.07 bar)
Air Inlet Size (quick connect)	1/4" NPT
Fluid Outlet Nozzle	1" OD
Estimated Evacuation Time	3 - 4 min.
Wetted Materials	Zinc Plated Steel, Steel, Viton®, HDPE, and PVC
Service Bulletin	SB 4027

MODELS AVAILABLE	DESCRIPTION
<b>4110-022</b>	Roughneck II™ Used Oil Drain
<b>4110-023</b>	Roughneck II™ Used Anti-freeze Drain
<b>4140-064</b>	Replacement Drain Bowl