

Used Fluid Equipment

Truck Drain and Drain-Pit Boss

The truck drain comes pre-assembled allowing for immediate use. Includes "used oil only" and "used anti-freeze only" decals for fluid identification. Connects to a used oil evacuation system using a cam-lock kit and evacuation system.

The Pit Boss rolling pit drain captures used fluids. Specifically designed to easily roll on guide tracks in the user's pit and connect to a used fluid evacuation system.

The low volume truck drain comes pre-assembled allowing for immediate use. Connects to a used oil evacuation system using a 3/4" cam-lock kit for anti-freeze or a 1" cam-lock kit for used fluid.

Features

Truck Drain

- Two fixed 8" wheels and one swivel caster
- Double baffles with upper screen and a catch lip help prevent fluid from splashing out
- Tubular U-handle design for excellent maneuvering
- All steel design

Low Profile Truck Drain

- Two anti-splash baffles, side splash guards and a metal catch screen. Select a 3/4" cam-lock kit for anti-freeze or a 1" cam-lock kit for used fluid

Pit Boss

- Two anti-splash baffles, side splash guards and a metal catch screen
- Front and rear drain ports
- 3" diameter wheels which are mounted to accommodate a pit track width of 34" to 53"
- Tool shelf below the tank for pit service tool
- All steel design



TECHNICAL DATA			
MODELS	4120-003 4120-004	4120-006	4140-060 4140-020
Tank Capacity	5.2 gal (20 l)	26 gal (98.4 l)	34 gal (128.7 l)
Fluid Outlet	4120-003 3/4" for anti-freeze 4120-004 1" for used oil	1"	4140-060 1" cam-lock nipple 4140-020 1" NPT(F) bare
Measurements	9" H x 15" W x 32" L	9" H x 24" W x 36" L	16.72" H x 28.4" W x 34" L, 2" adjustable unit height
Wetted Materials	Zinc Plated Steel, Steel, Viton, HDPE, and PVC	Zinc Plated Steel, Steel, Viton, HDPE, and PVC	Zinc Plated Steel, Steel, Viton, HDPE, and PVC
Service Bulletin	SB 4234	SB 4051	SB 4227

MODELS AVAILABLE	DESCRIPTION
4120-003	Low Profile Truck Drain for anti-freeze
4120-004	Low Profile Truck Drain for oil
4120-006	Low Profile Truck Drain Bare
4140-060	Drain - Pit Boss with Quick Connect Kit 4140-061
4140-020	Drain - Pit Boss Bare

Warning! Not to be used with flammable fluids.

CAM-LOCK COUPLER & NIPPLE RATED FOR 250 PSI (17 BAR)

Cam-Lock Coupler & Nipple		4140-044 Coupler 3/4" NPT(F)
		4140-017 Coupler 1" NPT(F)
		4140-054 Nipple 3/4" NPT(F)
		4140-055 Nipple 1" NPT(F)
		4140-045 Nipple 3/4" NPT(M)
		4140-018 Nipple 1" NPT(M)
		4140-046 Dust Cap 3/4" NPT(F)
		4140-019 Dust Cap 1" NPT(F)
		4140-052 Dust Plug 3/4" NPT(M)
		4140-053 Dust Plug 1" NPT(M)

CAM-LOCK COUPLER & NIPPLE RATED FOR VACUUM OR UP TO 3,000 PSI (207 BAR)

Cam-Lock Kits		4140-061 Cam-Lock Kit 1" for used oil for use with Pit Boss Bare 4140-020 Includes: Fluid Ball Valve, Cam-Lock nipple, Cap, and Hex nipple
		4140-067 Cam-Lock Kit 3/4" for anti-freeze for use with Pit Boss Bare 4140-020 Includes: Fluid Ball Valve, Cam-Lock nipple, Cap, and Hex nipple
Hose Kit for used oil evacuation		4140-013 Hose Kit for used oil evacuation Includes: 4140-017 - Cam-lock coupler 1", 8181-002X - Hose low pressure 2.5' x 1"