

# Diaphragm Pumps

## Product Selection Matrix

**Balcrank**  
Fluid Dispensing Systems

MAX. FREE FLOW	AIR INLET	FLUID IN / OUT	WETTED PARTS		RECOMMENDED FLUID TYPES	RECOMMENDED APPLICATIONS
			CHECK BALLS	DIAPHRAGM		
<b>CF10 POLYPROPYLENE</b>						
10 gal/min (38 l/min)	3/8" NPSM(F)	1/2" NPT(F)	PTFE (Teflon®)	Hytrell®	Anti-freeze (Glycol) and windshield wash solution	Fluid dispensing and transfer
<b>CF10 POLYPROPYLENE/DEF</b>						
10 gal/min (38 l/min)	3/8" NPSM(F)	1/2" BSPP(F)	PTFE (Teflon®)	Hytrell®	Diesel exhaust fluid	Fluid dispensing and transfer
<b>CF15 POLYPROPYLENE</b>						
15 gal/min (50 l/min)	3/8" NPSM(F)	1/2" NPT(F)	PTFE (Teflon®)	Hytrell®	Anti-freeze (Glycol) and windshield wash solution	Fluid dispensing, transfer, and evacuation
<b>CF15 POLYPROPYLENE MIX</b>						
15 gal/min (50 l/min)	2-3/8" NPSM(F)	1/2" NPT(F)	PTFE (Teflon®)	Hytrell®	Anti-freeze (Glycol) and windshield wash solution	Fluid dispensing, transfer, and evacuation
<b>CF15 POLYPROPYLENE/DEF</b>						
15 gal/min (50 l/min)	3/8" NPSM(F)	1/2" BSPP(F)	PTFE (Teflon®)	Hytrell®	Diesel exhaust fluid	Fluid dispensing and transfer
<b>CF15 ALUMINUM</b>						
15 gal/min (50 l/min)	3/8" NPSM(F)	1/2" NPT(F)	Buna-N™	Buna-N™	Light viscosity fluids synthetic, mineral oils, and oil	Fluid dispensing, transfer, and evacuation
<b>CF30 POLYPROPYLENE</b>						
28 gal/min (106 l/min)	3/8" NPSM(F)	1" NPT(F)	PTFE (Teflon®)	Hytrell®	Anti-freeze (Glycol) and windshield wash solution	Fluid dispensing, transfer, and evacuation
<b>CF30 POLYPROPYLENE/DEF</b>						
28 gal/min (106 l/min)	3/8" NPSM(F)	1" BSPP(F)	PTFE (Teflon®)	Hytrell®	Diesel exhaust fluid	Fluid dispensing and transfer
<b>CF30 ALUMINUM</b>						
28 gal/min (106 l/min)	3/8" NPSM(F)	1" NPT(F)	Hytrell®	Buna-N™	Light viscosity fluids synthetic, mineral oils, oil, and diesel	Fluid dispensing, transfer, and evacuation
<b>CF50 POLYPROPYLENE/DEF</b>						
53 gal/min (200 l/min)	3/8" NPSM(F)	1" ANSI FLANGE	Acetal	Hytrell®	Diesel exhaust fluid, Anti-freeze, (Glycol) and windshield wash solution	Fluid dispensing, transfer, and evacuation
<b>CF50 ALUMINUM</b>						
53 gal/min (200 l/min)	3/8" NPSM(F)	1" NPT(F)	Buna-N™	Buna-N™	Light viscosity fluids, synthetic, mineral oils, used oil, and diesel	Fluid dispensing, transfer, and evacuation
<b>CF65 ALUMINUM</b>						
65 gal/min (250 l/min)	1/2" NPSM(F)	1 1/2" NPT(F)	Acetal	Hytrell®	Light viscosity fluids, synthetic, mineral oils, used oil, windshield wash solution, and diesel	High volume transfer, bulk fill, de-watering, and evacuation

Pumps AODD

