

AODD

1" UL Aluminum 46 gal/min

1" UL Aluminum 46 gal/min Description

These conventional pumps may be used as stand-alone pumps for transfer applications or as system pumps that include hose reels.

Model 1120-015Y is UL79 listed for pumping: Diesel Fuel, No. 4 Fuel Oils (or lighter), Motor Oil, Kerosene, and Water.

1" UL Aluminum 46 gal/min Models Available

- ☐ **1120-015Y** 1" UL Aluminum AODD Pump

1" UL Aluminum 46 gal/min Specifications

- 3.1. AODD Pump will have an air inlet port of 3/8" NPT(F)
- 3.2. AODD Pump will have a fluid inlet port of 1" NPT(F)
- 3.3. AODD Pump will have a fluid outlet port of 1" NPT(F)
- 3.4. AODD Pump will have a free flow of 46.2 gal/min (175 l/min) based on 100 psi (6.8 bar) air pressure
- 3.5. AODD Pump will have an operating air pressure of 20 -100 psi (1.4-6.8 bar)

Materials

- 4.1. The wetted materials will consist of N = Nitrile, Z = PTFE

Warranty

- 5.1. The 1" UL Aluminum 46 gal/min will have a 1-year standard warranty on defects in materials and workmanship only.